


Rescue Sleds



MFCInternational
by RESPIREX

CONTENTS

3	RESCUE SLED
6	STANDARD REGULATOR
7	MASTER BLASTER INFLATER
8	BRAVO 2000 INFLATER
9	BRAVO FOOT PUMP
10	BRAVO HAND PUMP

RESCUE SLED



The RS series Rescue Sleds are flood water rescue craft for inshore crisis rescues and flooded urban and coastal areas. The Rescue Sled is available in five standard sizes 3, 5, 6, 10 & 15 person. The 3, 5 & 6 person sleds are ideal for swift-water and narrow access rescue.

The 10 & 15 person sleds are wider with a larger floor area and corresponding load capacity and are more suited for emergency evacuation situations.

FEATURES

- Lightweight and easily portable
- Easy to manoeuvre
- Can be paddled or pulled by hand
- Exceptionally Stable
- Can be used in shallow water (5cm+)
- Open low stern makes casualty recovery easier
- Easily used by wheelchair users
- Individuals can sit on the floor surrounded by the inflated tubes, providing a reassuring rescue environment
- Exceptionally tough and durable
- Rapid inflation and deployment
- Easily launched into the surf zone for sea rescue, with a raised bow for improved performance in waves
- Open stern for easy access and self-bailing

- Multiple D-rings for towing and line control
- Lifelines fitted down each side
- Carrying handles (x5)
- Minimal training, servicing and maintenance costs
- Choice of glued hypalon or welded TPU construction

USED FOR


- Crisis rescue
- Flood rescue
- River rescue
- Flooded coastal and urban areas
- Casualty recovery
- Shallow water rescue

RESCUE SLED

TECHNICAL DATA

	RS3	RS5	RS6	RS10	RS15
Product Code - Hypalon	WR0001	WR0002	WR0169	WR0003	WR0005
Product Code - TPU	WRW0001/01	WRW0002/01	WRW0169/01	WRW0003/01	WRW0005/01
No. of Persons	3	5	6	10	15
O.A Length (cm)	256	331	397	400	500
O.A Width (cm)	117	117	117	190	231
O.A Height (cm)	40	40	40	56	77
Floor Thickness (cm)	12.5	12.5	12.5	12.5	12.5
Tube Diameter Bow/Stern (cm)	23/15	23/15	23/15	35/23	46/23
Max. Load (kg)	240	400	480	800	1200
Working Pressure (bar)	0.2	0.2	0.2	0.2	0.2
No. of chambers	1 + floor	1 + floor	1 + floor	4 + floor	4 + floor
Air Requirements (ltr)	530	670	710	2000	3800
Pack Size (cm)	88 x 35 x 30	88 x 35 x 30	88 x 35 x 30	88 x 55 x 35	90 x 70 x 52
Est. Weight (kg) - Hypalon / TPU	17 / 15	19.5 / 17.5	20.5 / 18.5	35 / 31	50 / 45
Valise Code (included)	590018	590018	590018	590004	590011
Recommended Regulator	8 Bar				

DETAIL DRAWING



STANDARD EQUIPMENT

- Valise (see above for codes)
- Kayak paddles (190002)
- 1m delivery hose with C7 fitting (for use with regulator: HS-03-04-01-09-17)
- Repair kit (Hypalon: 600001, TPU: 600024)

OPTIONS AND ACCESSORIES


- Rear bolster (Hypalon: WR9088, TPU: WRW9088/001)
- T-handle paddles (190003)
- Stowage pocket (Hypalon: 530070, TPU: 530070/001)
- Customer logo (LETTERING)
- Inflation pumps (various options, see next page)
- 8 bar regulator (Regulator: RE0034, Regulator & Hose: RE0034/006)

RESCUE SLED


OPTIONS FOR INFLATION




B.A. Cylinder
(By others)




8 bar Regulator
(RE0034)
Regulator &
hose kit
(RE0034/006)




1m Delivery Hose
(Supplied with sled:
HS-04-05-01-16-06)




**Master Blaster
Electric Inflator**
(180041 - 240v)
(180042 - 110v)




**Bravo2000
Electric Inflator**
(180026)



**Bravo10 Foot
Pump**
(180006)



**Bravo 4 ALU R.E.D Hand
Pump**
(180001)



STANDARD REGULATOR



The Standard Regulator is designed to be used with an air cylinder to reduce the amount of pressure which is leaving the cylinder and entering the inflatable product.

The regulator contains a shut off valve which stops the air flowing through the hose.

FEATURES

- Manufactured to ISO 2503
- Max. Input pressure 300 Bar
- Available as a regulator only or with attached hose and coupling/fitting
- Supplied with padded storage box

USED FOR

- Reducing BA cylinder pressure for inflation of rescue equipment

SUPPLIED WITH

- Hard shell carry case

TECHNICAL DATA

8 BAR REGULATOR

Single Stage Regulator	8 bar
Product Code (regulator only)	RE0034
Product Code (regulator & 2m 'inflation' hose) <i>With C7 hose fitting for inflatable shelters, boats etc</i>	RE0034/006
Max. Pressure Gauge	0-400 / 300 bar
Working Gauge	0-16 / 8 bar
Max. Inlet Pressure	300 bar
Working Pressure	0-8 bar adjustable
Max. Output	30 m ³ /h compressed air at 8 bar
Pack Size (mm)	210 x 195 x 75
Weight (kg)	1.5
Outlet Coupling (regulator)	Series 26 Female

METRO MASTER BLASTER INFLATOR



The Master Blaster Inflator / Deflators twin motor assembly is ideal for rapid inflation of larger structures and inflatables.

The patent twin fan motor assembly ensures 100% duty cycle to ensure continuous inflation/deflation.

FEATURES

- The Master Blaster Inflator/Deflator has a robust outer steel casing with an optional choice of mounting platforms.
- Fitted with 2x heavy duty commercial 1200 Watt 5.5 Amp motors.
- The patent twin fan motor assembly ensures 100% duty cycle to ensure continuous inflation/deflation.
- 12 month warranty
- Low maintenance with just regular cleaning/changing of the foam filter to ensure good airflow to cool the motor & prevent overheating, ensuring long life.

USED FOR

- Inflation/deflation of our inflatable product range

TECHNICAL DATA	240 Volt AC Model	110 Volt AC Model
Part No:	180041	180042
Construction:	All Steel	All Steel
Motor:	8.0 peak HP, (two motors)	8.0 peak HP, (two motors)
Airflow:	297 m/s	58,000 ft/min
Fan:	2-Stage Dual Fan	2-Stage Dual Fan
Power:	2160 Watts	2160 Watts
Current Draw:	9 Amps	18 Amps
Hose:	1.5m x 38mm Heavy Duty Hose	5ft x 1.5" Heavy Duty Hose
Nozzle:	Nozzle and Bayonet Connector	Nozzle and Bayonet Connector
Cable:	3.6m Heavy Duty	12ft Heavy Duty
Plug:	13A 240V UK or 2 Pin European	16A 110V 4h OP44 plug
Filter:	Foam Filter (Washable)	Foam Filter (Washable)
Dimensions:	550 x 260 x 165mm	21.7 x 10.25 x 6.5"
Weight:	7.95 kg	17.5 lbs

BRAVO 2000 ELECTRIC INFLATOR



The Bravo 2000 electric inflator consists of a main motor and a supplementary (booster) motor, which increases the capacity and pressure. The two motors can run simultaneously to obtain maximum capacity and pressure.

On the Bravo 2000, you can press the orange button to just run the main motor, or you can press the red button to switch on the booster to help obtain maximum performance. Both motors are protected by thermal fuses.

FEATURES

- Inflates and deflates
- Has a robust outer steel casing for additional protection
- Fitted with main motor and a booster motor to increase capacity and pressure
- 3m integral mains power lead comes with 2 pin plug*
- Comes with an inflation hose, 7 different adapters and a shoulder carry strap

USED FOR

- Inflation/deflation of our inflatable product range

TECHNICAL DATA

Bravo 2000 Electric Inflator	
Product Code	180026
Voltage Supply	230V (Main Motor) 230V (Booster)
Max. Power	1000W / 2000W
Max. Pressure	140 mbar (2 psi) / 400 mbar (5.8 psi)
Max. Flow Rate	1200 l/min / 2000 l/min
Dimensions	32 x 17 x 26 cm
Weight	4.1 kg

BRAVO FOOT PUMP



The Bravo 10 foot pump utilises an innovative design to make inflating and deflating a tube as effortless as possible. It has two chambers, one 5 litre (high volume, low pressure) which inflates to 2.1 psi and one 1.6 litre (low volume, high pressure) which inflates to 4.4 psi.

It also features an over inflation warning system in the form of a visual pressure indicator, crush resistant hose, anti slip feet and valve adapters. Manufactured from strong nylon reinforced fibreglass, this provides a powerful, lightweight pump which is unaltered by exposure to the sun and sea environment.

FEATURES

- Manufactured from strong nylon reinforced fibreglass
- Unaffected by the sun or sea environment
- Lightweight due to the use of synthetic materials
- Features four antislip feet for greater stability
- Supplied with a non-kink hose and a selection of interchangeable valve adaptors and nozzles

USED FOR

- Inflation/deflation of our inflatable product range

TECHNICAL DATA

Bravo 10 Foot Pump

Product Code	180006
Materials	Nylon Reinforced Fibreglass
Capacity	5 ltr (normal pressure) / 1.6 ltr (high pressure)
Dimensions	35 x 25 x 8 cm
Max. Pressure	800 mbar (11.6 psi)
Weight	1.9 kg
Colour	Grey with Yellow Hose*

BRAVO 4 ALU R.E.D. HAND PUMP



The Bravo 4 ALU R.E.D (Reduced Effort Device) is a double action hand pump that automatically adjusts for easier pumping.

The hand pump automatically switches to downward pumping only once the pressure exceeds 400 mbar (5.8 psi), allowing you to blow up your inflatable product quickly and efficiently.

FEATURES

- A powerful double action hand operated pump with a double chamber allowing a maximum of 4000cc (2 x 2000cc)
- Automatically changes from double to single action at 400 mbar (5.8 psi) to reduce effort at higher pressures
- Features an aluminium shaft handle for durability
- Anti-sand cover gasket

- Inflates and deflates
- Pressure up to 800 mbar (11.6 psi)
- Supplied with non-kink hose and a selection of interchangeable valve adaptors and nozzles

USED FOR

- Inflation/deflation of our inflatable product range

TECHNICAL DATA

Bravo 4 ALU R.E.D Hand Pump

Product Code	180001
Materials	Plastic with aluminium shaft handle
Capacity	2 x 2000 cc
Dimensions	11 x 22 x 47 cm
Max. Pressure	800 mbar (11.6 psi)
Weight	0.75 kg
Colour	Blue*

* Note: Colour of product may vary.

Maintenance Instructions

Please be sure that before and during the use, the pump is fully lubricated by oil.

To lubricate the pump, open the ring nut and spread a thin layer of oil or grease on the gasket and the tube.





MFCInternational
by RESPIREX

MFC International Ltd

Naval Yard, Tonypandy,
Rhondda Cynon Taff, CF40 1JS
🌐: www.mfc-international.com
☎: +44 (0) 1443 433 075
✉: sales@mfc-international.com