



The Scoprega GE 25 electric inflator/deflator consists of a main motor and a supplementary compressor, which increases the maximum inflation pressure.

The GE 25 includes a pressure gauge through which the target inflation pressure is set; the two inflation stages will then run automatically to reach the required inflation pressure and stop once it has been reached.

FEATURES

- Double Stage electric inflator for high pressure applications, HVHP
- Automatic switch from turbine to double compressor stage
- Easy setting of the desired pressure and pressure control through manometer, automatic stop
- Inflation fittings available for the most common valves
- Carry bag included

USED FOR

- Inflation/deflation of our inflatable product range

TECHNICAL DATA

Scoprega GE 25 Electric Inflator

Product Code	190009
Voltage Supply	230V AC 50Hz
Plug	Schuku (European) UK Adapter P/N: 180012/TYPE C
Max. Pressure	Turbine 80mbar/1.15psi, Compressor 1.5bar/22psi
Max. Flow Rate	Turbine 450 l/min, Compressor 250 l/min
Dimensions (in bag)	41 x 21 x 27 cm
Weight	6 kg



COMPATIBLE WITH

- Rescue Sleds (all)
- Evacuation Raft (all)
- Rescue Craft & Multi-Function Craft (all)
- Jet Ski Rescue Board
- Airtrack Rescue Paths (all)
- Animal Rescue Paths (all)
- Inflatable Stretcher
- API Stretcher (all)
- Inflatable Decontamination Showers (all)
- Inflatable Shelters (all)
- Inflatable Reservoir